



Emergency exit opening request device

CLEV3

CLEV3 is a remote part associated with ALLIGATOR UGCIS. The unit complies with standards NF S 61-934 and NF S 61-935.

Emergency unlocking of an electrically locked exit is possible by possible :

- either by local action on the Opening Request Device (DDO) placed near the exit and resulting in automatic unlocking after a time delay of a time delay of 8 seconds (T1). An additional time delay of 3 minutes (T2) can be obtained from the UGCIS. Unlocking then takes place after a visual alarm has been triggered of the exit concerned.
- or via the keypad code for authorised opening,

Recommended for :

public buildings, administrations, airports.

Functional characteristics

- Opening request device for 1 DAS lock compliant with NF S 61-937 with 3 states: standby, security, safety
- Management of safety mode in the absence of people (depending on DAS, electrical and/or mechanical maintenance of locking, infinite time delay)
- Management of an audible signal
- Management of an visual signal
- Management of an external control input for access control
- Management of potential-free repeat contacts
- 12-key keypad for :
 - resetting the CLEV following an action on its opening request device,
 - management of internal access control according to a passage mode or permanent mode,
 - access to the CLEV's internal programming.
- Protective shutter associated with an audible signal and a pre-alarm on the UGCIS
- Protective shutter seal (optional)



Electrical characteristics

- Operating power supply :
 - 15 to 30 Vdc / 24 Vdc nominal
 - consumption: 150 mA +/-20% at 24 Vdc
- Remote control power supply :
 - 24 or 48 Vdc, depending on the DAS used
- Consumption 3.5 W maximum per DAS
- Consumption in safety position: depending on the DAS used

Mechanical characteristics

- Dimensions: H240 x W97 x D60 mm
- Housing colour: light grey RAL 7035
- Protection rating: IP42
- Weight: 480 g
- Operating temperature : -10° C to +50° C
- Permitted relative humidity: < 92

Associable DAS

- DAS Alligator NF S 61-937 (3 states) with position contacts
- Compatibility with other makes: consult us